



- ES Luminaria realizada en extrusión de aluminio. Disponible para lámpara dicróica o LED de Ø50mm.
- EN Recessed spotlight. Made of extruded aluminium. Available for Ø50mm, dichroic lamp or LED.
- DE Strahler aus Aluminium extrusion. Erhältlich für dichroitische Lampe oder LED von Ø50mm.
- FR Luminaire en extrusion d'aluminium. Pour 1 ampoule dycroïque ou LED de Ø50mm.
- RU Встраиваемые внимания. Изготовлен из экструдированного алюминия. Доступно для Ø50mm, дихроичных лампы или LED.

General



IP20



850°C



300

LED

w	lum	mA	CRI
6	600	350	>85
10	1.000	700	>85

Power

● LED	□ 230V	LED	600lm / 6W	CBES	A	06	*	*	4	*	**
			1000lm / 10W	CBES	A	10	*	*	4	*	**
△ PAR 16	□ 230V	GU 10	Max. 50W	CBES	E	50	X	X	X	X	**

LED Control

⏻	N	No Dimmable	CBES	*	**	N	*	*	*	*	**
LC	C	Dimmable IGBT/Triac	CBES	*	**	C	*	*	*	*	**
push 1-10V	F	Dimmable 1-10 V / Push	CBES	*	**	F	*	*	*	*	**

LED Colour Temperature

☀	3	3000° K	CBES	*	**	*	*	3	*	*	**
☀	4	4000° K	CBES	*	**	*	*	4	*	*	**

LED Beam Angle

40°	4	Medium 40°	CBES	*	**	*	*	*	4	*	**
-----	----------	------------	------	---	----	---	---	---	----------	---	----

Complements

○	B	Clear Diffuser	CBES	*	**	*	*	*	*	B	*
---	----------	----------------	------	---	----	---	---	---	---	----------	---


Colours

□	WS	Satin White	CBES	*	**	*	*	*	*	*	WS
□	BS	Satin Black	CBES	*	**	*	*	*	*	*	BS
□	AL	Aluminium	CBES	*	**	*	*	*	*	*	AL



Photometric Data

LED 6W 40°



PAR 16 50W 40°

LED 10W 40°

